



Balusters

Square Balusters



Round Balusters




BALUSTRADING

- Balusters are manufactured from 25 Mpa reinforced concrete.
- Reinforcing extends from the bottom of the baluster by approx 100mm.
- Between 4 and 5 balusters are required per metre, depending on the height and thickness of the baluster and the overall visual symmetry of the end result. In all cases the relevant municipal requirements should be consulted with particular reference to safety.
- When a purpose made balustrade plinth is utilised, the position of each baluster is predetermined by holes cast into the plinth. Where no plinth is used the positions of the baluster holes must be set out and drilled manually.
- Balusters are fixed using a tile adhesive and riversand in equal parts. Sufficient adhesive should be utilised to fill the fixing hole and cover the area of the base of each baluster. Register each baluster to a line at the base, and a fishline strung at the top between the first and last balusters of a particular run. Plumb each baluster individually, using wood wedges where necessary.
- Allow to strengthen before installing the coping.
- Fix the coping using the same adhesive as for the balusters. Apply sufficient adhesive to cover the tops of all the balusters making contact, and the end face of the coping. Allow a joint of 5mm to 10mm. Use a fishline to ensure a neat result. Where applicable, set up two corners and then the fishline, working towards one end. One coping will require cutting and should be positioned one full length away from the end of a run. In some cases a very short cut length will be necessary. If this length is not fully supported by two balusters then it is to be discarded and two lengths must be cut, sharing out the short cut between them.
- When installing long straight runs, or in critical areas, alternate lengths of coping should be drilled and fixed with a single steel pin and epoxy, into the top of a baluster.

DISCLAIMER


The above information is intended as a guide to the correct installation of precast concrete balustrading, and Old World Concretes (Pty) Ltd can in no way hold itself responsible for any installation not undertaken by its own representatives.

Balustrade Plinths



BALUSTRADE PLINTH MK1

1,200m
Holes at 240mm
CORNER
CURVES As per pricelist.




BALUSTRADE PLINTH MK2

880mm
Holes at 220mm centres
CURVES As per pricelist
CORNER & FAIR END.



Baluster Piers




Balustrade example using Baluster Piers 600, 700 and 800, Model 3 and Model 3mk2 Balusters, Plettenberg Coping, Balustrade Plinth MK2, and Baluster Pier Cap.

BALUSTERS		GREY	
		Excl.	Vat 15%
PWV Delivery 10%			
MODEL 3	600h x 25kg	168.00	193.20
MODEL 3 Mk2	700h x 28kg	216.00	248.40
MODEL 5	610h x 25kg	183.00	210.45
MODEL 6	735h x 33kg	189.00	217.35
MODEL 8	400h x 11kg	120.00	138.00
MODEL 10	585h x 14kg	177.00	203.55
MODEL 11	845h x 30kg	218.00	250.70
MODEL 12	540h x 15kg	153.00	175.95
MODEL 13	870h x 26kg	218.00	250.70
MODEL 14	533h x 14kg	153.00	175.95
MODEL 15	667h x 11kg	189.00	217.35
MODEL 16	457h x 14kg	126.00	144.90
MODEL 18	460h x 12kg	126.00	144.90
MODEL 19	510h x 14kg	148.00	170.20
MODEL 20	736h x 20kg	177.00	203.55
MODEL 20 Mk2	870h x 2xkg	218.00	250.70
MODEL 22	880h x 31kg	218.00	250.70
MODEL 23	645h x 12kg	183.00	210.45
MODEL 24	600h x 16kg	163.00	187.45
MODEL 25	740h x 22kg	193.00	221.95

Certain balusters are available in half (priced as a whole)

BALUSTRADE PLINTHS		EACH	
		Excl.	Vat 15%
PWV Delivery 10%			
Mk 1	1,200m x 380mm x 100mm	582.00	669.30
CORNER	360mm x 360mm	308.00	354.20
CURVES	1m radius x 580mm	308.00	354.20
	2,500m radius x 680mm	363.00	417.45
	2,6m radius x 660mm	351.00	403.65
	3,0m radius x 680mm	363.00	417.45
	3,300m radius x 930mm	496.00	570.40
	4,0m radius x 690mm	367.00	422.05
	4,8m radius x 690mm	367.00	422.05
	5,7m radius x 680mm	363.00	417.45
	7,500m radius x 720mm	382.00	439.30
	9,600m radius x 930mm	496.00	570.40
Mk 2	880mm x 305mm x 75mm	375.00	431.25
CORNER	310mm x 310mm	282.00	324.30
FAIR END		375.00	431.25
CURVES	1,200m radius x 660mm	303.00	348.45
	2,000m radius x 660mm	303.00	348.45
	3,300m radius x 660mm	303.00	348.45
	7,400m radius x 660mm	303.00	348.45
	9,600m radius x 660mm	303.00	348.45

BALUSTRADE PIERS		EACH	
		Excl.	Vat 15%
PWV Delivery 10%			
BALUSTER PIER 600		402.00	462.30
BALUSTER PIER 700		472.00	542.80
BALUSTER PIER 800		542.00	623.30
BALUSTER PIER 600/700 CAP		167.00	192.05
PLETTENBERG PIER		1,819.00	2,091.85



BALUSTER PIER 600 & 700 & 800


For 600 and 700mm high balusters
Optional Capping extra.

PLETTENBERG BALUSTER PIER


920mm high




Copings for Balustrades




RESIDENCY 200 Throated
 Length 1,220m
 CURVES As per pricelist
 SWEEP-DOWN
 Drop 150mm x 610mm long
 FAIR END 1,220m o/l




BUCKINGHAM Throated
 Length 1,200m
 CURVES As per pricelist
 FAIR END 1,200m o/l




RESIDENCY 200 PLAIN
 Length 1,220m




PLETTENBERG COPING
 Length 1,000m
 CURVES As per pricelist
 FAIR END 745mm o/l (700mm bed)




PINMILL
 Length 1,000m
 CORNER
 FAIR END 750mm o/l



DROSTDY MAJOR Throated
 Length 1,000m
 FAIR END
 CORNER



DROSTDY Throated
 Length 1,000m
 CURVES As per pricelist
 FAIR END 1,000m o/l



DROSTDY PLAIN
 Length 1,000m

COPINGS FOR BALUSTERS & SINGLE BRICK WALLS		EACH	
		Excl.	Vat 15%
N.B. Price per metre is for easy comparison only. Sold in lengths as specified below.		PWV delivery 10%	
Extra per cut		119.00	136.85
BUCKINGHAM	1,200m	320.00	368.00
BUCKINGHAM CORNER	365 x 365mm	183.00	210.45
BUCKINGHAM FAIR END	1,200m	413.00	474.95
BUCKINGHAM CURVE	1,200m radius x 930mm	284.00	326.60
	1,500m radius x 720mm	227.00	261.05
	2,000m radius x 1,040mm	329.00	378.35
	2,550m radius x 705mm		
	3,500m radius x 840mm	267.00	307.05
	6,500m radius x 615mm		
	9,600m radius x 660mm	210.00	241.50
DROSTDY Plain	1,000m	159.00	182.85
DROSTDY Throated	1,000m	213.00	244.95
DROSTDY Throated CORNER	335 x 335mm	183.00	210.45
DROSTDY Throated FAIR END	800mm	238.00	273.70
DROSTDY Throated CURVE	1,250m i/s rad. x 965mm	264.00	303.60
	2,400m i/s rad. x 945mm	257.00	295.55
	3,300m i/s rad. x 860mm	232.00	266.80
DROSTDY MAJOR Throated	1,000m	262.00	301.30
DROSTDY MAJOR Throated CORNER		183.00	210.45
DROSTDY MAJOR Throated FAIR END		274.00	315.10
PINMILL	1,000m	244.00	280.60
PINMILL CORNER		176.00	202.40
PINMILL FAIR END	750mm o/l length	270.00	310.50
PLETTENBERG	1,000m	295.00	339.25
PLETTENBERG CORNER		183.00	210.45
PLETTENBERG FAIR END	745mm o/l	324.00	372.60
PLETTENBERG CURVE	0,75m radius x 660mm	221.00	254.15
	1,0m radius x 600mm	221.00	254.15
	1,5m radius x 600mm	221.00	254.15
	2,0m radius x 660mm		
	2,6m radius x 660mm	244.00	280.60
	3,2m radius		
	4m radius x 680mm	248.00	285.20
	5m radius x 660mm	244.00	280.60
	5,7m radius x 700mm	259.00	297.85
	7,3m radius		
	9,3m radius x 920mm	340.00	391.00
RESIDENCY 200 Plain	1,220m	207.00	238.05
RESIDENCY 200 Throated	1,220m	269.00	309.35
RESIDENCY 200 Throated CORNER	360 x 360mm	183.00	210.45
RESIDENCY 200 Throated FAIR END	1,220m	363.00	417.45
RESIDENCY 200 Throated CURVE	400mm i/s rad. x 580mm	227.00	261.05
	1,220m i/s rad. x 675mm	227.00	261.05
	2,000m i/s rad. x 910mm	299.00	343.85
	3,400m i/s rad. x 950mm	302.00	347.30
	4,400m i/s rad. x 875mm	280.00	322.00
	5,500m i/s rad. x 1,070m	340.00	391.00
	7,540m i/s rad. x 970mm	303.00	348.45
	8,700m i/s rad. x 980mm	308.00	354.20
RESIDENCY 200 SWEEPDOWN	610mm	289.00	332.35

