

Column Caps & Bases

COLUMN CAPS and BASES		EACH	
		Excl.	Vat 15%
Column Caps & Bases when purchased separately are priced as follows:		PWV delivery 10%	
Extra for cutting in half		97.00	111.55
For 230mm diameter Shaft	One piece		
Doric Cap	230od/185h/355sq/160hole	284.00	326.60
Doric Base	230od/120h/320sq/140hole	284.00	326.60
Tuscan Cap	250od/115h/345sq/160hole	225.00	258.75
Tuscan Base	260od/150h/325sq/160hole	254.00	292.10
For 250mm diameter Shaft	One piece		
Doric Cap	260od/185h/355sq/220hole	382.00	439.30
Doric Base	260od/150h/360sq/220hole	363.00	417.45
Tuscan Cap	270od/130h/340sq/220hole	295.00	339.25
Tuscan Base	270od/130h/340sq/220hole	295.00	339.25
For 280mm diameter Shaft	One piece		
Doric Cap	290od/230h/465sq/220hole	444.00	510.60
Doric Base	300od/185h/355sq/185hole	395.00	454.25
Tuscan Cap or Base Thin	312od/115h/405sq/200hole	298.00	342.70
Tuscan Base MK2 Thick	310od/215h/405sq/200hole	345.00	396.75
For 320mm diameter Shaft	One piece		
Doric Cap	320od/270h/505sq/220hole	571.00	656.65
Doric Base	370od/230h/515sq/280hole	509.00	585.35
Tuscan Cap	340od/150h/460sq/220hole	381.00	438.15
Tuscan Base	340od/200h/460sq/220hole	446.00	512.90
For 320mm square Shaft	One piece. Also for SESTR		
Sestri Egg & Dart Cap or Base	315od/230h/490sq/NA hole	1,048.00	1,205.20
Sestri Plain/Swept Cap or Base	320od/150h/410sq/NA hole	527.00	606.05
For 400mm diameter Shaft	One piece. Also for COLOSSUS		
Doric Cap	435od/250h/570sq/320hole	1,302.00	1,497.30
Doric Base	430od/245h/565sq/320hole	1,302.00	1,497.30
Corinthian Cap	410od/530h/760sq/320hole	2,097.00	2,411.55
Corinthian Base	420od/340h/780sq/320hole	1,842.00	2,118.30
Roman Cap	430od/250h/770sq/320hole	1,779.00	2,045.85
Tuscan Cap	425od/140h/570sq/320hole	740.00	851.00
Tuscan Base	425od/205h/550sq/320hole	788.00	906.20
For 450mm diameter Shaft	In two halves		
Doric Cap	475od/295h/590sq/380hole	1,686.00	1,938.90
Doric Base	450od/250h/590sq/380hole	1,525.00	1,753.75
For 500mm diameter Shaft			
Doric Cap (Halves)	525od/320h/710sq/450hole	1,873.00	2,153.95
Doric Base (Halves)	525od/350h/695sq/450hole	1,873.00	2,153.95
Enriched Doric Cap (Halves)	500od/700h/800sq	2,671.00	3,071.65
Roman Cap (Solid)	500od/240h/800sq/380 hole	1,942.00	2,233.30
Tuscan Cap or Base (Solid)	510od/200h/635sq/380hole	1,431.00	1,645.65
For 550mm diameter Shaft	In two halves		
Tuscan Cap or Base	580od/200h/690sq/340hole	1,552.00	1,784.80
For 600mm diameter Shaft	In two halves		
Doric Cap	605od/315h/800sq/505hole	2,444.00	2,810.60
Doric Base	605od/350h/780sq/505hole	2,444.00	2,810.60
For 700mm diameter Shaft	In two halves		
Doric Base	750od/420h/900sq/620hole	2,710.00	3,116.50

NB. These Caps and Bases are not designed to "clip" onto or around an existing shaft.

All either position above/below the shaft at time of casting or require a 55mm recess to be cast or cut into the shaft for subsequent installation of the Cap/Base.

If you do not have a recess for the Cap/Base then the next bigger Cap/Base could be used but it is likely to look too big.

If you require the Cap/Base to fit around the shaft then please discuss your requirement with our sales staff before ordering.

See following page for "clixon" Caps and Bases designed to be retrofitted to the Everite standard range of columns.



Glass Reinforced Concrete Caps and Bases on following page



GLASS REINFORCED CONCRETE (GRC) COLUMN CAPS and BASES	EACH	
	Excl.	Vat Incl.
These caps and Bases are designed for retrofitting to an already installed standard Everite non-tapered pipe. All in halves	PWV delivery 10%	
For 318mm outside diameter shaft		
Tuscan Cap 340od/150h/460sq/320hole	512.00	588.80
Tuscan Base 340od/200h/460sq/320hole	531.00	610.65
For 368mm outside diameter shaft		
Tuscan Cap 400od/150h/520sq/370hole	613.00	704.95
Tuscan Base 400od/200h/520sq/370hole	651.00	748.65
For 530mm outside diameter shaft		
Doric Cap 605od/315h/800sq/535hole	P.O.A	
Doric Base 605od/350h/780sq/535hole	P.O.A	



In-Situ cast columns supplied and installed by Old World Concretes (Pty) Ltd.

In-Situ Cast Columns

These columns must be cast in-situ. Typically, the main contractor would provide scaffolding, steel reinforcing, and sand and stone. Old World Concretes, as subcontractor, positions the bases, erects the scaffolding and the column shutter, supplies the cement and mixes the concrete, and casts the shaft (in two or three lifts) all to the indicated levels. Lastly, after moving the shutter to the next position, the cap is placed on the shaft and the complete column is finished off.

Where there is no main contractor Old World Concretes will supply everything necessary for an additional cost.

In all cases a single phase power supply must be provided.

COLUMN TYPE 600/500

This column has a shaft diameter at its base of 600mm and at its neck of 500mm. The maximum shaft length is 5500mm which can be cast as short as 4800mm and still maintain reasonable proportions. Taken in combination with the caps and bases available, the maximum height is 6550mm (base 350/ shaft 5500/ cap 700). The minimum height of column, overall, is 5215mm (base 215/ shaft 4800/ cap 200).

The selection of caps and bases is illustrated on the following page.

COLUMN TYPE 500/500 (No Taper)

This column has a shaft diameter at its base of 500mm and at its neck of 500mm. The maximum shaft length is 5500mm and can be cast any shorter length. Taken in combination with the caps and bases available, the maximum height is 6170mm (base 350/ shaft 5500/ cap 320). The selection of caps and bases is illustrated on the following page.

COLUMN TYPE 500/410

This column has a shaft diameter at its base of 500mm and at its neck of 410mm. The maximum shaft length is 4600mm which can be cast as short as 4000mm and still maintain reasonable proportions. Taken in combination with the caps and bases available, the maximum height is 5480mm (base 350/ shaft 4600/ cap 530). The minimum height of column, overall, is 4410mm (base 200/ shaft 4000/ cap 210).

The selection of caps and bases is illustrated on the following page.

COLUMN TYPE 410/320

This column has a shaft diameter at its base of 410mm and at its neck of 320mm. The maximum shaft length is 3800mm, the minimum is 2600mm. Taken in combination with the caps and bases available, the maximum height is 4500mm (base 245/ shaft 3800/ cap 440). The minimum height is 3010mm (base 210/ shaft 2600/ cap 200).


The selection of caps and bases is illustrated on the following page.



By Old World Concretes.
In-situ cast columns,
Woodlands Lintels,
Number 13 Balusters with
plinth and coping.



IN-SITU CAST COLUMNS



In Situ 410/320 In Situ 500/410 In Situ 500/500 In Situ 600/500

